


Specifications



MODELS	GS™-3390 RT		GS™-4390 RT		GS™-5390 RT	
	US	Metric	US	Metric	US	Metric
Working height max*	39 ft	12.06 m	49 ft	15.11 m	59 ft	18.15 m
A Platform height max	33 ft	10.06 m	43 ft	13.11 m	53 ft	16.15 m
B Platform length - outside, extended:						
single deck	17 ft 6.25 in	5.34 m	17 ft 6.25 in	5.34 m	17 ft 6.25 in	5.34 m
dual deck	21 ft 6.5 in	6.57 m	21 ft 6.5 in	6.57 m	21 ft 6.5 in	6.57 m
C Platform width - outside	6 ft	1.83 m	6 ft	1.83 m	6 ft	1.83 m
Platform height - stowed**	5 ft 1 in	1.55 m	5 ft 11 in	1.80 m	6 ft 7.5 in	2.02 m
D Height - stowed	8 ft 10.5 in	2.71 m	9 ft 7.5 in	2.93 m	10 ft 4 in	3.15 m
rails lowered	6 ft 7.75 in	2.03 m	7 ft 4.75 in	2.25 m	8 ft 1.25 in	2.47 m
E Length - stowed:						
single deck	12 ft 11.25 in	3.94 m	12 ft 11.25 in	3.94 m	—	—
dual deck	13 ft .5 in	3.98 m	13 ft .5 in	3.98 m	—	—
with outriggers	16 ft	4.88 m	16 ft	4.88 m	16 ft	4.88 m
Length - extended:						
single deck	17 ft 8.5 in	5.40 m	17 ft 8.5 in	5.40 m	17 ft 8.5 in	5.40 m
dual deck	21 ft 6.5 in	6.57 m	21 ft 6.5 in	6.57 m	21 ft 6.5 in	6.57 m
F Width -						
standard tires	7 ft 6 in	2.29 m	7 ft 6 in	2.29 m	7 ft 6 in	2.29 m
high flotation tires	8 ft 5 in	2.57 m	8 ft 5 in	2.57 m	8 ft 5 in	2.57 m
G Wheelbase	9 ft 4 in	2.84 m	9 ft 4 in	2.84 m	9 ft 4 in	2.84 m
H Ground clearance - center	1 ft 2 in	.36 m	1 ft 2 in	.36 m	1 ft 2 in	.36 m

PRODUCTIVITY						
Lift capacity	2,500 lbs	1,134 kg	1,500 lbs	680 kg	1,500 lbs	680 kg
Lift capacity - extension deck	500 lbs	227 kg	500 lbs	227 kg	500 lbs	227 kg
Drive speed - stowed	5.0 mph	8.0 km/h	5.0 mph	8.0 km/h	5.0 mph	8.0 km/h
Drive speed - raised	0.7 mph	1.1 km/h	0.7 mph	1.1 km/h	0.7 mph	1.1 km/h
Gradeability***	50%		50%		40%	
Turning radius - inside	7 ft 1 in	2.16 m	7 ft 1 in	2.16 m	7 ft 1 in	2.16 m
Turning radius - outside	17 ft 6 in	5.33 m	17 ft 6 in	5.33 m	17 ft 6 in	5.33 m
Controls	proportional		proportional		proportional	
Raise / lower speed	45 / 29 sec		45 / 39 sec		55 / 49 sec	
Tires - foam-filled rough terrain	12 x 33 in	30 x 84 cm	12 x 33 in	30 x 84 cm	12 x 33 in	30 x 84 cm
Tires - high flotation air-filled	16 x 33 in	41 x 84 cm	16 x 33 in	41 x 84 cm	16 x 33 in	41 x 84 cm

POWER						
Power source	Ford gas/LPG 82 hp (61.1 kW) Deutz diesel F3L 2011 49 hp (36 kW), air cooled					
Fuel tank capacity	30 gal	113.6 L	30 gal	113.6 L	30 gal	113.6 L
Hydraulic system capacity	30 gal	113.6 L	30 gal	113.6 L	30 gal	113.6 L

WEIGHT****						
	12,085 lbs	5,482 kg	13,086 lbs	5,936 kg	16,616 lbs	7,537 km

STANDARDS COMPLIANCE						
	ANSI A92.6, CSA B354.2, CE Compliance, AS 1418.10					

* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.
 ** Based on RT tires. Deduct 2 in (5.8 cm) for turf and non-marking tires.
 *** Gradeability applies to driving on slopes. See operator's manual for details regarding slope ratings.
 **** Weight will vary depending on options and/or country standards.

Features

EASILY CONFIGURED TO MEET YOUR NEEDS

PLATFORM

- Dual slide-out extension deck package
5 ft (1.52 m) front and 4 ft (1.22 m) rear

POWER OPTIONS

- Ford gas/LPG 82 hp (61.1 kW)
- Deutz diesel 49 hp (36 kW)

DRIVE

- 4WD

TIRE OPTIONS

- Foam-filled rough terrain tires (standard)
- High flotation air-filled tires
- Non-marking tires

STANDARD FEATURES

MEASUREMENTS

GS™-3390

- 39 ft (12.06 m) working height
- Up to 2,500 lb (1,134 kg) lift capacity

GS™-4390

- 49 ft (15.11 m) working height
- Up to 1,500 lb (680 kg) lift capacity

GS™-5390


- 59 ft (18.15 m) working height
- Up to 1,500 lb (680 kg) lift capacity

PRODUCTIVITY

- 5 ft (1.52 m) slide-out extension deck (GS™-4390)
- Diamond plate deck (GS™-4390)
- Proportional lift and drive
- Onboard diagnostic system
- AC power to platform
- Two self-closing gates
- Electric horn
- Automatic leveling hydraulic outriggers (GS™-5390)
- Tilt sensor with audible alarm
- Descent alarm
- Oscillating axle (GS™-3390)
- Hour meter
- Full-time positive traction control
- Four-wheel drive
- Slide-out engine tray
- Foam-filled rough terrain tires

POWER

- 12 V DC auxiliary power
- Meets current emissions standards



OPTIONS & ACCESSORIES

PRODUCTIVITY

- Dual slide-out extension deck package
- Automatic leveling hydraulic outriggers (GS™-3390, -4390)
- Air line to platform
- Platform work lights
- Pipe cradle (pair)
- Dual flashing beacons
- Motion alarm

POWER

- 2000 watt generator (110 V / 60 Hz)
- Cold start packages
- Diesel scrubber/spark arrestor
- Diesel spark arrestor (without scrubber)
- Hydraulic oil cooler
- LPG steel tank only, 33.5 lb capacity
- LPG tank kit (carrier with tank)

Genie United States

18340 NE 76th Street
P.O. Box 97030
Redmond, Washington 98073-9730

Telephone **(425) 881-1800**
Toll Free in USA/Canada **800-536-1800**
Fax (425) 883-3475

Genie Europe

The Maltings
Wharf Road
Grantham NG31 6BH
U.K.

Telephone **+44 (0)1476 584333**
Fax +44 (0)1476 584334

Email: infoeurope@genieind.com

Distributed By:

For further information, please contact your local distributor or the Genie Industries sales office listed. Continuous improvement of our products is a Genie policy. Product specifications are subject to change without notice or obligation. The photographs and drawings in this brochure are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. Prices and specifications subject to change without notice. The only warranty applicable is the standard written warranty applicable to the particular product and sale. Genie makes no other warranty, expressed or implied. Products and services listed may be trademarks, service marks or trade-names of TEREX Corporation and/or its subsidiaries in the USA and other countries and all rights are reserved. Copyright © 2005 Genie Industries, Inc. "Genie" is a Registered Trademark of Genie Industries, Inc. in the USA and many other countries. Genie is a TEREX Company.